

WINFIELD

400 High Grove Blvd.
Glendale Heights, IL 60139
Phone: 847.437.4000
winfieldwall.com

Barclay Butera Living in Style Installation Instructions

- Surface Preparation:** All surfaces must be clean, dry, smooth and structurally sound. Sand finish plaster must be scraped smooth. Cinder or cement block must be plastered or cemented before application of wallcovering. Newly plastered walls must be thoroughly dry before application.
- Usual wall preparation is satisfactory except on asbestos board and other highly alkaline surfaces, such as cement block and portland cement plaster. Walls that are tightly sealed with several coats of paint must be opened with rough sandpaper or steel wool to allow adhesive to dry.
- Application:**
1. Before cutting and hanging, check color, condition, quantity, and quality. Be certain pattern and color are as ordered. Be sure that there is sufficient material to complete the job. No allowances will be given for cut material. Check each roll for uniform shading.
- Should you have any questions, contact your local Kravet sales representative, Kravet showroom or Winfield Wallcovering at 800-486-6800 before proceeding. Even through great care has been taken in the production of this wallcovering, variations in texture and color can occur.
2. For patterns with a definite design (such as a floral or damask), do not reverse the strips. Some patterns may have a more subtle design characteristic than others. By first laying two strips together on the table or floor prior to pasting, the proper match can be determined. On random textures or non-directional stripes, reverse each strip. The match and design of each pattern determines whether it should be reversed or not.
 3. The walls should be properly sized and primed. A pre-mixed, heavy-duty vinyl adhesive (i.e. Roman Pro 732) should be used by the installer. Do not dilute.
 4. Apply the recommended adhesive to the back of the material using either a pasting machine or paint roller. Fold each end towards the middle, pasted sides together, aligning the edges carefully so they do not dry out. Do not crease the material. Allow the material to book for 10 minutes. This will allow the adhesive to penetrate the fabric backing, which is important for a successful installation.
 5. Use strips in exact order as they are cut from the roll. Fill in over doors and windows as they come with strips cut in consecutive order from the roll. Hang only 1-2 strips at a time.
 6. Smooth material to hanging surface with a plastic smoothie or soft bristle to eliminate air bubbles and ensure adhesion. Remove paste immediately from surface with clean warm water using a clean cloth. Change the water often. Allow paste at seams to dry before cleaning to prevent seams from opening.
 7. STOP AFTER APPLYING 3 STRIPS. If there are any variations in color and/or color match, this should be immediately communicated to your local Kravet sales representative, Kravet showroom, or Winfield Wallcovering for inspection before proceeding further with installation.

For additional information contact Winfield Wallcovering Customer Care at 800.486.6800

Barclay Butera Living in Style Wallcovering is Marketed Nationally by Kravet Inc.